

Maximum versatility for precise CO₂ energy delivery.



The BEACON Advanced Energy
Laser combines our industryleading Enhanced Safety Fibers
with free beam energy delivery,
giving you the versatility to choose.


System Features:

Versatile: Industry-leading enhanced safety fibers + Line of Sight (LOS) capabilities.

Easy-to-Use: OR workflow inspired user interface with smartphone like navigation.

Built for Performance: Innovative design ensures mobility with integrity. Multiple laser modes enable desired tissue interaction.

OmniGuide's polymer-based Enhanced Safety Fibers feature multiple layers of highly reflective mirrors, which efficiently transmit aser energy the length of the fiber.





BEACON Offers the Latest Advancement in Smart CO₂ Laser Technology

Versatile

Easy-to-Use

Built for Performance

Dual laser options to accommodate surgical preferences

- Designed to exclusively support OmniGuide's polymer-based Enhanced Safety Fibers
- Line of Sight option provides multiple configurations via lockable Articulating Arm



BEACON's lockable Articulating Arm

User friendly interface

- High-Definition display screen with advanced range of motion
- OR workflow inspired interface
- Intuitive, smartphone like navigation
- Audio & Visual guidance features to enhance user experience





Sample screens from BEACON Graphical User Interface

Mobility with integrity

- Internal optical components isolated from vibration
- Enables portability without inconvenience of misalignment

Multiple laser modes for desired tissue interaction

- 3 Output Modes: Continuous, Single Pulse, & Repeat Pulse
- Available in Continuous wave & SuperPulse settings



BEACON's multiple lasing modes

SKU	Description	BEACON Specifications	
420060-AA	60W Laser with Articulating Arm	Laser Wave Length:	10,600 nm
420030-AA	30W Laser with Articulating Arm	Output Power:	Fiber Adapter: 30 W Maximum
420031	AccuBeam EasySpot Micromanipulator		Articulating Arm: 60 W Maximum
420070	AccuBeam MicroSpot Micromanipulator	Connectors:	Fiber Adapter: custom ST connector
420035	Incisional Hand Piece - 75mm		Articulating Arm: 15/16-12 female thread
420037	Incisional Hand Piece - 125mm	Weight:	68 kg (150 lbs - laser only)
420039	Incisional Hand Piece - 250-450mm	Size (WxDxH):	49 x 49 x 144 cm (20" x 20" x 59")
420046	Direct Coupler	Operating Voltage/Current:	120 / 240 volts

^{*} Note: additional Mounts for MicroManipulators, Incisional Hand Piece lengths, Adapters and Lens Assemblies available upon request

For more information call 888-666-4484 or visit www.omni-guide.com

OmniGuide and OmniGuide Surgical are registered trademarks of OmniGuide, Inc. All content is copyright of OmniGuide, Inc. © 2018 See www.omni-guide.com/patents for information about the coverage of this OmniGuide product by U.S. and/or foreign patent rights. 1-0168-034-07-00 rev. 0 To request copies use: DOC-BEACON-1

- **&** 888.666.4484 | 617.551.8444
- □ customerservice@omni-guide.com
- www.omni-guide.com
 www.omni-guide.comni-guide.com
 www.omni-guide.com
 www.omni-guide.com
 w

